

R260

SKID LOADERS



GEHL®

| Capacities | | Metric | Imperial |
|--|-----|-------------------------|-------------------------|
| Rated Operating Capacity | | 1179 kg | 2599 lb |
| Rated Operating Capacity with Optional Counterweight | | 1261 kg | 2780 lb |
| Unladen weight | | 3719 kg | 8199 lb |
| Weight and dimensions | | | |
| Overall Operating Height - Fully Raised | h27 | 4089 mm | 161 in |
| Height to Hinge Pin - Fully Raised | h28 | 3124 mm | 123 in |
| Overall Height to top of ROPS | h17 | 2057 mm | 81 in |
| Dump angle at full height | a5 | 40 ° | 40 ° |
| Dump height | h29 | 2388 mm | 94 in |
| Overall length with bucket | l16 | 3632 mm | 143 in |
| Dump reach - Full height | r6 | 686 mm | 27 in |
| Rollback at ground | a13 | 28 ° | 28 ° |
| Seat to ground height | h30 | 1016 mm | 40 in |
| Wheelbase | y | 1257 mm | 49 in |
| Overall width less bucket | b1 | 1711.96 mm | 67 in |
| Bucket Width | e1 | 1711.96 mm | 67 in |
| Ground clearance | m4 | 203 mm | 8 in |
| Overall length - Less Bucket | l2 | 2832 mm | 111 in |
| Clearance Radius - Front with Bucket | b18 | 2286 mm | 90 in |
| Clearance Circle - Front without Bucket | b19 | 1422 mm | 56 in |
| Clearance Circle - Rear | wa1 | 1626 mm | 64 in |
| Performances | | | |
| Travel Speed with Two-Speed Option - Maximum | | 19.20 km/h | 12 mi/h |
| Travel speed (unladen) | | 12.90 km/h | 8 mi/h |
| Wheels | | | |
| Standard tyres | | 12.00x16.5 HD | 12.00x16.5 HD |
| Engine | | | |
| Engine brand | | Yanmar | Yanmar |
| Engine model | | 4TNV98CT-NMSLV Stage V | 4TNV98CT-NMSLV Stage V |
| Engine norm | | Stage V | Stage V |
| Gross Power (kW) | | 53.70 kW | 53.70 kW |
| Net Power (kW) | | 52.70 kW | 52.70 kW |
| Max. torque / Engine rotation | | 294 Nm / 1625 rpm | 217 ft/lbs / 1625 rpm |
| Battery voltage | | 12 V | 12 V |
| Starter (kW) | | 3 kW | 3 kW |
| Hydraulics | | | |
| Standard flow - Auxiliary hydraulics | | 90 l/min | 24 US gpm |
| High-Flow Auxiliary Hydraulics - Option | | 132.50 l/min | 35 US gpm |
| Tank capacities | | | |
| Fuel tank | | 81.40 l | 22 US gal |
| Reservoir Capacity Hydraulics | | 30.30 l | 8 US gal |
| Displacement | | 3.30 l | 0.87 US gal |
| Noise and vibration | | | |
| Environmental noise (LwA) | | 101 dB | 101 dB |
| Whole-Body Vibration (ISO 2631-1) | | 0.96 m/s ² | 0.96 m/s ² |
| Vibration to whole hand/arm | | < 1.50 m/s ² | < 1.50 m/s ² |



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend