

V210 - NEW

SKID LOADERS



GEHL®

Capacities		Metric	Imperial
Operating Capacity At 50% Tipping Load		952.54 kg	2100 lb
Operating Weight		3393 kg	7480 lb
Unladen weight		3045 kg	6713 lb
Tipping capacity		1905 kg	4200 lb
Weight and dimensions			
Operating Weight - Approximate		3393 kg	7480 lb
Overall Operating Height - Fully Raised	h27	4013 mm	158 in
Height to Hinge Pin - Fully Raised	h28	3061 mm	121 in
Overall Height to top of ROPS	h17	2032 mm	80 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2286 mm	90 in
Overall length with bucket	l16	3543 mm	139 in
Dump reach - Full height	r6	851 mm	34 in
Rollback Angle at Full Height	a4	92 °	92 °
Seat to ground height	h30	952.50 mm	37 in
Overall width less bucket	b1	1623 mm	64 in
Ground clearance	m4	178 mm	7 in
Overall length - Less Bucket	l2	2743 mm	108 in
Clearance Radius - Front with Bucket	b18	2146 mm	84 in
Clearance Circle - Rear	wa1	1664 mm	66 in
Performances			
Travel Speed with Two-Speed Option - Maximum		18.70 km/h	12 mi/h
Travel speed (unladen)		12.10 km/h	8 mi/h
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98C-NGL	4TNV98C-NGL
Engine norm		Tier 4	Tier 4
Gross Power (kW)		52.70 kW	52.70 kW
Net Power (kW)		51.70 kW	51.70 kW
Max. torque / Engine rotation		241 Nm / 1625 rpm	178 ft/lbs / 1625 rpm
Number of cylinders		4	4
Engine cooling system		Water	Water
Battery voltage		12 V	12 V
Alternator - Ampere		100 A	100 A
Starter (kW)		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		86.50 l/min	23 US gpm
Auxiliary Hydraulic Pressure		239.59 bar	3475 PSI
High-Flow Auxiliary Hydraulics - Option		114 l/min	30 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		229.25 bar	3325 PSI
Tank capacities			
Fuel tank		106 l	28 US gal
Displacement		3.30 l	0.87 US gal



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend